

Multi-Hazard Suppression Systems



AH-02120



AH-03233

AH-03232

AH-02120 Multi-Hazard Suppression Control Panel

- This compact and esthetic unit is ideally suited for a variety of agent-releasing applications such as FM-200, CO₂, Dry & Wet Chemical.
- Large unit accommodating more zones are also available.
- Agent can be releasing automatically or manually.
- System enables highly reliable monitoring and suppression control.
- Audible and visible indication when system has fault condition.
- Digital release countdown.

Specifications

Model	AH-02120
Power	220V AC/50Hz *Others also available
Battery Capacity	24V DC 4Ah
Zone Voltage	24V DC
EOL Resistance	10kΩ
Detection Type	Cross-zone detection
# of heat detectors connected	No limit *Except electronic-type
# of smoke detectors connected	30/zone *Horing Lih manufactured
Dimensions	420mm(H) x 380mm(W) x 130mm(D)
Color	Ivory

AH-03233 Releasing Indicator

- The display can be set according to customer's requirements.

Specifications

Model	AH-03233
Supply Voltage	24V DC 670mA (bulb) 310mA (LED)
Light Source	1W bulb x 18 or ø5 LED RED x 28
Display Type	Non-flash
Material	0.8mm stainless steel
Color	Red
Dimensions	155mm(H) x 405mm(W) x 60mm(D)

AH-03232 Manual Pull Station

- Emergency Start/Stop switch, Auto/Manual key switch.
- Power LED, Releasing LED, Start LED, Stop LED, Auto LED, and Manual LED.
- Digital release countdown.

Specifications

Model	AH-03232
Supply Voltage	24V DC
Material	1.2mm stainless steel
Color	Red
Dimensions	160mm(H) x 165mm(W) x 50mm(D)

Approvals:

Approvals: