



# AH-9717

## Manual Call Point

# AH-0217

## Manual Call Point




### AH-0217 Features

- Available in flush or surface mounted models.
- Plastic film on glass.
- Test key inserted from bottom.
- Suitable for the majority of conventional fire alarm system.
- Clear protection cover is also available (optional).
- Choice of red, yellow, blue or green finish also available for custom-made.

### AH-9717 Features

- Emergency press alarm, immediately activates fire alarm signal.
- Indicator light above fire alarm push-button confirms the alarm signal transfer.
- There are a phone jack and reset button behind the cover cap.
- Type I is simultaneous dual loop, Type II is simultaneous dual signal transfer (refer to diagram below)
- Optional base is available.

Approvals: EN54  

Approvals: 

### Specifications

Model	AH-0217	AH-9717
Operating Power	-	24V DC 30mA
Operating Contact	6A 125/250VAC	Max. 30V DC 500mA
Resistance	30mΩ	-
Ambient Temperature	-25°C ~ +85°C	-
Sub-function	-	Phone jack, confirmation lamp, reset button.
Material	-	Fire-proof plastic
Dimensions	88mm(H) x 88mm(W) x 52mm(D)	140mm(Dia.) x 45mm(H)
Weight	About 165g	About 160g

