

AH-05316

Addressable Fire Alarm Control Panel



Characteristics

- Large LCD screen (40 x 15 lines) allows more events to be displayed on the same screen.
- Loop device can be set up to be temporarily isolated.
- Optional thermal printer that can printout complete panel status.
- Individual loop module test feature to save time on panel test.
- On-board Self-test feature for simulating alarm output.
- Easy system programming through PC to panel.
- Events log can store up to 1023 events.

Specifications

Model	AH-05316
Power	220V AC 50Hz *Others also available
Battery Capacity	24V DC 4Ah
Charging Voltage, Current	26V DC 100~400mA *With auto adjustment function
Zone Voltage, Current	24V DC short circuit under 5V 30mA
System Capacity	127 devices/1 loop *Expandable for site requirement
Exterior Resistance	Round-trip under 50Ω
Transmitting Method	Digital series transmitting
Transmitting Range	Up to 1000 meters
Accumulation Time	4~40 seconds *Other options available
Main Sound	90dB @1M
# of conventional heat detectors connected	No limit *Except electronic-type
# of conventional smoke detectors connected	20/zone *Horing Lih's product
Material	1.6mm steel plate
Color	Pearl gray
Dimensions (mm) H x W x D	1~4 loop: 400 x 500 x 130 5~8 loop: 600 x 500 x 150

Approvals: 