


# AH-0633

## Mechanical Rate of Rise Heat Detector



### Characteristics

- The standard detector is 2-wire or 3-wire. For 4-wire type just add one relay output module. Simple and easy module placement enables wider application and flexible stock control.
- Detector is made of high endurance, solid and colorfast Fire-proof plastic.
- Non-loosening screws on base terminal for easy installation.
- Dual LEDs for 360-degree visibility.

### Specifications

Model	AH-0633-2	AH-0633-3	AH-0633-4
Alarm Contact	N/A	N/A	0.8A @30V DC 0.4A @125V AC
Voltage Range	12 ~ 30V DC		
Alarm Current @24V DC 470Ω	40mA	40mA	45mA
Alarm Temperature	Comply to EN54		
Ambient Temperature	0°C ~ +55°C		
Material	Fire-proof plastic		
Dimensions	102mm(Dia.) x 52mm(H)		
Weight	140g	140g	155g
Color	White		

### Effective alert area

Construction/Height	Under 4M	4M ~ 8M
Fire-proof Building	90 M <sup>2</sup>	45 M <sup>2</sup>
Ordinary Building	50 M <sup>2</sup>	30 M <sup>2</sup>

### Order information

AH-0633-2	2-wire
AH-0633-3	3-wire with remote indicator output
AH-0633-4	4-wire with relay output

Approvals: 